




PANEL5000-D152-T

Touch Screen Monitor



15.1" XGA Resistive Touch Screen
Industrial Monitor

PANEL5000-D152-T




Specifications:

General	Control button	Set Contrast ratio and Luminance via OSD at the back panel
	Dimensions (W x H x D)	393mm x 317mm x 53mm (15.47" x 12.48" x 2.09")
	Drill Hole Size (W x H)	376mm x 302mm (14.80" x 11.89")
	Box structure	Front panel: aluminum-magnesium alloy, anodized coating ;Back cover: SGCC, Ground isolation protection
	Mounting	Support Embedded,wall-mounted,Desktop and VESA mounting
	Power Supply	DC 12V,support reverse polarity protection, (optional DC 24V)
	Power Dissipation	10W
	Signal input	VGA & DVI-D
	NW	-
LCD	LCD Size	15" XGA TFT
	Resolution	1024 x 768
	Colors	16.7MB
	Active Area (W x H)	304.13mm x 228.10mm (11.97" x 8.98")
	Backlight	LED
	MTBF	30000hrs
	Pixel Pitch(H x V)	0.297 x 0.297
	Luminance	420cd/m ²
	Contrast Ratio	800 : 1
	Viewing Angle	(L) 80 / (R) 80 / (T) 80 / (B) 80
Touchscreen	Type	Resistive touch screen
	Resolution	4096 x 4096
	Transmittance	> 81%
	Controller interface	USB/ RS-232C
	Driver Support	Windows XP, Windows 7, Winows8, Windows 10, Linux
	Response Time	< 5ms
	Surface Hardness	Mohs' Number 3H
	Click life	250g / 35,000,000 times
	Draw life	250g / 5,000,000 times
Environmental	Work Temperature	-20 ~ 60° C (-4~140 °F)
	Storage Temperature	-30 ~ 80℃ (-22 ~ 176 °F)
	Relative humidity	5~95% (Non condensation)
	Shake	SSD applied: 1.5 Grms, IEC 60068-2-64, random, 5 ~ 500 Hz, 1 hr/axis
	Shock	SSD applied: 10 G, IEC 60068-2-64, Half-sine wave, 11ms duration
	EMC	CE/FCC Class A
	Water-proof	Front panel IP65


Touch Screen Monitor

Dimensions:

Unit : mm



I/O:



Interface Definition:

A:USB port
B:DC IN(12V)
C:DVI port
D:VGA port

Ordering Information:

Product Code	Description
PANEL5000-D152-TU	15"TFT LCD/Flat five-wire Resistive Touch Screen/DC12V input/1024*768
PANEL5000-D152-TS	15"TFT LCD/Flat five-wire Resistive Touch Screen(RS232 Model) /DC12V input/1024*768
PANEL5000-D152-TUW	15"TFT LCD/Flat five-wire Resistive Touch Screen/9~30V wide voltage input/1024*768
PANEL5000-D152-TSW	15"TFT LCD/Flat five-wire Resistive Touch Screen(RS232 Model) /9~30V wide voltage input/1024*768

Optional Equipment:

VGA Cable	3M/5M
DVI Cable	3M/5M
USB Cable	3M/5M
Power Line	3M/5M
HDMI turn DVI	3M/5M

Packing List:

Adapter	Adapter 12V/3.33A,40W 2pin Phoenix terminal
VGA Cable	1.8m
USB Cable	1.8m
Power Line	Chinese standard Power Line PSB-10+ST3
Touch Pen	Touch Pen
Hook	4*Hooks apply to Thickness=1mm~1.2mm

Touch Screen Monitor