

◆ **INPUT CHARACTERISTICS:**

- VOLTAGE: 90VAC ~ 264 VAC
- FREQUENCY: 50 ~60 HZ
- INPUT CURRENT: 8~5 A (RMS)
- INRUSH CURRENT: 80 A MAX



◆ **SPECIFICATION:**

- EFFICIENCY: 80% MAXIMUM, FULL LOAD CONDITION AT 230 VAC INPUT.
- POWER GOOD SIGNAL: ON DELAY TIME 100 ~ 500 ms, OFF DELAY TIME 1ms.
- HOLD UP TIME: 17ms AT 25% FULL LOAD CONDITION AT 115/230 VAC INPUT.
- OPERATING TEMPERATURE RANGE: 5 ~ 50 °C.
- REMOTE ON/OFF CONTROL: THE POWER SUPPLY OUTPUT SHALL BE ENABLED WITH AN ACTIVE-LOW TTL SIGNAL. WHEN TTL SIGNAL IS LOW, THE DC OUTPUTS ARE TO BE ENABLED. WHEN TTL SIGNAL IS HIGH OR OPEN CIRCUITED, THE DC OUTPUTS ARE TO BE DISABLED.
- OVER POWER PROTECTION: AT 115/230 VAC INPUT THE POWER SUPPLY WILL SHUT DOWN ALL DC OUTPUT WITH IN 105% TO 150% OF FULL LOAD.
- OVER VOLTAGE PROTECTION: +5V ±7.0V, +12V1,2 ±15.6V, +3.3V ±4.3V.
- EMI REQUIREMENT: FCC PART 15 SUB PART J CLASS B AT SYSTEM LOAD, CISPR 22 CLASS B.
- SAFETY: CE, TÜV, CB, UL(QQGQ2) , cUL(QQGQ8), FCC and BSMI
- DIMENSION: 140 (D) x 150 (W) x 86 (H) mm.
- COOLING: ONE 80\*25mm DC FAN.
- ACTIVE POWER FACTOR CORRECTION: EN 61000-3-2: 1995+A1+A2: 1998, CLASS D.

◆ **OUTPUT CHARACTERISTICS:**

OUTPUT VOLTAGE	OUTPUT CURRENT		REGULATION		OUTPUT	
	MIN [A]	MAX [A]	LOAD	LINE	RIPPLE MAX [P-P]	NOISE MAX [P-P]
+5V	1.0	30	±5%	±1%	50mV	50mV
+12V1	1.0	16	±5%	±1%	120mV	120mV
+12V2	1.0	16	±5%	±1%	120mV	120mV
+3.3V	1.0	28	±5%	±1%	50mV	50mV
-12V	0	0.8	±10%	±1%	150mV	150mV
-5V	0	0.3	±10%	±1%	100mV	100mV
+5VSB	0	2.5	±5%	±1%	50mV	50mV

1. MAXIMUM CONTINUOUS COMBINED LOAD ON +5V AND +3.3V OUTPUTS SHALL NOT EXCEED 150W(30A). +12V1 AND +12V2 OUTPUTS SHALL NOT EXCEED 324W (27A). -12V AND -5V OUTPUTS SHALL NOT EXCEED 10W.
2. MAXIMUM CONTINUOUS COMBINED LOAD ON +5V, +3.3V AND +12V OUTPUTS SHALL NOT EXCEED 440 W.
3. MAXIMUM CONTINUOUS TOTAL DC OUTPUT POWER SHALL NOT EXCEED 460W.